

Replaces: 2005-07-20 Date: 2014-10-08

# Limtvätt

Used to remove residue from dispersion-, contact- and resin adhesive. Also suitable for mixing in cleaning water to remove adhesive pressed out when installing wall or flooring material. Nonwater-based content. Intended for removing residue when gluing PVC, linoleum and polyolefin mats to floors, and PVC sheeting on walls.

- Water soluble
- Removes various adhesive

#### **TECHNICAL DATA**

Type: Mixture of solvents and tensides

**Consistency:** Clear, thin liquid **Density:** Approx. 800 kg/m<sup>3</sup>

Solvents: Isopropyl alcohol, acetone, ethanol,

distillates, hydrotreated light

Flash point: < 23°C

## **APPLICATION DATA**

Work temperature: +15°C to +25°C

Storage time: 12 months in sealed packaging. Store in

a cool, frost-free place.

Tools: Cloth

#### **HEALTH AND THE ENVIRONMENT**

Labelling

Highly flammable. Hazardous on inhalation, skin contact and ingestion. Store out of the reach of children. Store well away from sources of ignition. No smoking. Good ventilation essential. If insufficient ventilation cannot be established, we recommend using breathing apparatus with a Class A filter. Do not dispose of in public drains. Contains aromatic hydrocarbons, 10–30%.

Handling and cleaning instructions Avoid open flames and sparks.

For additional information, see the Safety Data Sheet.

#### **INSTRUCTIONS FOR USE**

Casco Limtvätt is intended for removing adhesive residue and stains that have dried. When removing these, use Casco Limtvätt in concentrated form. Apply Casco Limtvätt. Leave to work for a few minutes. Rub with a cloth or, in tougher cases, a scouring pad. Wipe up the dissolved adhesive residue. Clean with water and wipe down with a clean cloth. It may sometimes be necessary to leave Casco Limtvätt to work for 10–15 minutes.

NB If the product is left to work for too long, it may damage the surface of delicate materials. Casco Limtvätt is not suitable for sensitive surfaces such as those painted with alkyd or oil paints, untreated wood, etc. We recommend performing a preliminary test.

Casco Limtvätt can be mixed with water to loosen adhesive residue from wallpaper joins. Mix 1–2 parts Casco Limtvätt with 10 parts water. On application, follow the instructions presented above.

# **PACKAGING**

1 litre



This information is based on laboratory reports and extensive practical experience. The information is intended for users and designed to help them identify the most appropriate work method.

As the production conditions of the individual user is beyond our control, we accept no liability for the actual result of the work, affected by local circumstances. In every case, we recommend testing and ongoing checks

## Certified according to:



**Sika Sverige AB** 163 08 Spånga, Sweden Tel. +46 8 621 79 00 Web: www.casco.com